

ZMIERZCHOWE



CZUJNIKI ZMIERZCHOWE

CZ: snímač soumraku/ SK: snímač súmraku/ EN: twilight sensor



A



B



C



D



E

	INDEX	Max. load	AC 230V	Light level	IP	Light level	L x W x H	
A	011587	300W	AC 230V	5-15Lux	IP44	Biały biły white	125 x 78.8mm	5902216786578
B	011584	400W	AC 230V	5-50Lux	IP44		82x125 mm	5902216786585
C	221	300W	AC 230V	5-50Lux	IP54		56.8x37.3x24mm	5902216786615
D	222	300W	AC 230V	2-100Lux	IP65	Szary Šedý Grey	90x66x35mm	5902216786622
E	6747	300W	AC 230V	2-100Lux	IP65		63.4x48x27.3mm	5902216786608



40000 h



IN



Materiał / Materiál / Material

PL: Tworzywo sztuczne PC

CZ: PC Plast

SK: PC Plast

EN: PC Plastic

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -10°C do +25°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -10 ° C to + 25 ° C

humidity: <85% pressure: 690-1060 hPa

Uwagi / Komentář / Komentáre

PL: Kąt działania czujnika 360°

CZ: Rozsah čidla pohyblu 360°

SK: Uhol činnosti pohybového čidla 360°

EN: Sensor angle 360°

BroLux