

ALCOTT – AC LED



HIGH BAY LED

CZ: Průmyslová svítidla LED HIGH BAY / SK: Priemyselná lampa / EN: LED high bay



	INDEX			Lm	Lm			A [mm]	[mm]	C [mm]	
A	010576	Alcott LED	60W	5 100 lm	85 lm/W	4500 K	Srebrny Stieborný stříbrná silver	279	225	230	5902216710559
A	010562	Alcott LED	60W	5 100 lm	85 lm/W	5700 K		279	225	230	5902216719248
B	010574	Alcott LED	90W	9 900 lm	110 lm/W	5700 K		279	305	230	5902216710030
B	010608	Alcott LED	90W	9 900 lm	110 lm/W	4500 K		279	305	230	5902216719231
C	010616	Alcott LED	120W	13 200 lm	110 lm/W	4500 K		279	385	230	5902216710047
C	010529	Alcott LED	120W	13 200 lm	110 lm/W	5700 K		279	385	230	5902216701243
D	010617	Alcott LED	150W	16 500 lm	110lm/W	4500 K		279	465	230	5902216710054
D	008955	Alcott LED	150W	16 500 lm	110 lm/W	5700 K		279	465	230	5902216701236

AC 230V	Power LED	60°	NON-DIM
≥70	40000 h	IP 65	IN&OUT
≥0.95			

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -10°C do +25°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -10 ° C to + 25 ° C

humidity: <85% pressure: 690-1060 hPa

BroLux