

# ALCOTT - AC LED



## LAMPA ULICZNA LED

CZ: LED pouliční lampa/ SK: LED pouličné lampy/ EN: LED street lamp



		INDEX				PF	Tc[K]		A [mm]	B [mm]	C [mm]	
A		010498	ALCOTT LED	60W	5100 lm	≥0.95	5700 K	Srebrny Stieborný stříbrná silver	232	279	175	5902216719255
A		010552	ALCOTT LED	60W	5100 lm	≥0.95	4500 K		232	279	175	5902216710061
B		010509	ALCOTT LED	90W	9900 lm	≥0.95	5700 K		312	279	175	5902216713901
B		010535	ALCOTT LED	90W	9900 lm	≥0.95	4500 K		312	279	175	5902216719262
C		010514	ALCOTT LED	120W	13200 lm	≥0.95	5700 K		392	279	175	5902216710078
C		010534	ALCOTT LED	120W	13200 lm	≥0.95	4500 K		392	279	175	5902216710085
D		008966	ALCOTT LED	150W	16500 lm	≥0.95	5700 K		472	279	175	5902216713918
D		010530	ALCOTT LED	150W	16500 lm	≥0.95	4500 K		472	279	175	5902216713925

AC 230V	Power LED	120°	IP
≥70	50000 h	65	RoHS COMPLIANT
CE	RoHS		

### Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -10°C do +25°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -10 ° C do + 25 ° C

vlhkosť: <85% tlak: 690-1060 hPa

SK: teplota: od -10 ° C do + 25 ° C

vlhkosť: <85% tlak: 690-1060 hPa

EN: temperature: from -10 ° C to + 25 ° C

humidity: <85% pressure: 690-1060 hPa

**BroLux**