

BOLD



NAŚWIETLACZ LED

CZ: vedl světlomet / SK: vedie svetlomet / EN: LED floodlight



INDEX	ABC	AC	Lm	lm/W	Beam	Tc[K]	Beam	Dimensions			Barcode
								A [mm]	B [mm]	C [mm]	
045517	Bold	50 W	6500 lm	128lm/W	70°x140°	4000 K	Czarny Černá Čierny Black	180	150	27	5902808809098
045521	Bold	50 W	6500 lm	128lm/W	90°	4000 K		180	150	27	5902808810056
045522	Bold	50 W	6500 lm	128lm/W	70°x140°	5500 K		180	150	27	5902808809104
045518	Bold	100 W	13000 lm	128lm/W	70°x140°	4000 K		270	222	27	5902808809111
045523	Bold	100 W	13000 lm	128lm/W	70°x140°	5500 K		270	222	27	5902808809128
045519	Bold	150 W	19500 lm	128lm/W	70°x140°	4000 K		330	274	32,5	5902808809135
045524	Bold	150 W	19500 lm	128lm/W	70°x140°	5500 K		330	274	32,5	5902808809142
045526	Bold	200 W	26000 lm	128lm/W	70°x140°	2700 K		400	333	32,5	5902808809159
045520	Bold	200 W	26000 lm	128lm/W	70°x140°	4000 K		400	333	32,5	5902808809166
045525	Bold	200 W	26000 lm	128lm/W	70°x140°	5500 K		400	333	32,5	5902808809173

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -10°C do +25°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -10 ° C to + 25 ° C

humidity: <85% pressure: 690-1060 hPa



AC 230V

SMD LED

>80

IP

IK



65

08



Brolux

www.bowi.com.pl