

BROQUE



TRACK LIGHT

CZ: Lištové svídlidlo COB LED / SK: Lištové svietidlo COB LED / EN: track light



A



B



	INDEX	ABC		Lm	Lm	Tc[K]			Rodzaj szyny zasilania	A [mm]	B [mm]	
A	5389	BROQUE	30W	1260 lm	81 lm/W	4000 K	24°		1-fazowa	78	118	5902808805724
B	003259	BROQUE	30W	1260 lm	81 lm/W	4000 K	24°			78	118	5902808805717

AC 230V	COB	IP	PF
CRI(Ra)	40000 h	20	>0,5

Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -10°C do +25°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -10 ° C to + 25 ° C

humidity: <85% pressure: 690-1060 hPa

BroLux

www.bowi.com.pl