

CYNIDECO

OPRAWY LED

CZ: LED svítidlo/ SK: LED svietidlo/ EN: LED lamp

A



B



	INDEX	ABC				Tc[K]		A [mm]	B [mm]	C [mm]	
A	5385	Cynideco LED	30W	2400 lm	80 lm/W	4000K	Biały bielá white	1200	70	40	5902216758063
B	003345	Cynideco LED	30W	2400 lm	80 lm/W	4000K	Czarny Černá Čierny Black	1200	70	40	5902808807865



AC 230V

SMD LED

120°



IP



>70

40000 h

20

PF



CE



0.5

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C do +60°C

humidity: <85% pressure: 690-1060 hPa

Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

Brulux