

EDOM



OPRAWY LED

CZ: LED svítidlo/ SK: LED svetidlo/ EN: LED lamp



A

B



	INDEX	ABC	INDEX	Lm	Lm	Tc[K]	PF	INDEX	INDEX	INDEX	INDEX	INDEX
A	013720	Edom LED	24 W	2640 lm	100lm/W	4000K	Biały Bílá Bielá White	0,9	600	90	70	5902808805922
A	009201	Edom LED	36 W	2800 lm	78 lm/W	4000K		0,9	1200	90	70	5902216793132
A	013718	Edom LED	40 W	4400 lm	110 lm/W	4000K		0,9	1200	90	70	5902808805946
B	013721	Edom LED	24 W	2640 lm	100 lm/W	4000K	Czarny Černá Čierny Black	0,9	600	90	70	5902808805939
B	009214	Edom LED	36 W	2800 lm	78 lm/W	4000K		0,9	1200	90	70	5902216793149
B	013719	Edom LED	40 W	4400 lm	110 lm/W	4000K		0,9	1200	90	70	5902808805953



AC 230V

SMD LED

120°



IP

IK

UGR

80

20

06

21



RoHS
COMPLIANT

Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkosť: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkosť: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C to +60°C

humidity: <85% pressure: 690-1060 hPa

BroLux