

# GREEN



## LAMPA ULICZNA LED

CZ: LED pouliční lampa/ SK: LED pouličné lampy/ EN: LED street lamp





Driver

LED



Power reduction



INDEX	ABC				PF	Tc[K]		A [mm]	B [mm]	C [mm]	
006699	GREEN LED	20 W	2 600 lm	130 lm/W	0.95	4000 K	Szary Šedá Šedá Grey	551	244	193	5902808800842
009276	GREEN LED	30 W	3 900 lm	130 lm/W	0.95	4000 K		551	244	193	5902808800859
006708	GREEN LED	40 W	5 200 lm	130 lm/W	0.95	4000 K		551	244	193	5902216712058
009277	GREEN LED	50 W	6 500 lm	130 lm/W	0.95	4000 K		551	244	193	5902808800866
006709	GREEN LED	60 W	7 800 lm	130 lm/W	0.95	4000 K		620	285	95	5902216712065
006710	GREEN LED	70 W	9 100 lm	130 lm/W	0.95	4000 K		551	244	193	5902216712072
006723	GREEN LED	80 W	10 400 lm	130 lm/W	0.95	4000 K		551	244	193	5902808800873
003561	GREEN LED	100 W	13 000 lm	130 lm/W	0.95	4000 K		745	285	95	5902216735774



AC 230V



SMD3030



60x120°



>80



66



08



IN&OUT



68 mm



Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C to +60°C

humidity: <85% pressure: 690-1060 hPa

Brolux

www.bowi.com.pl