

KARADAM



HIGH BAY LED

CZ: Průmyslová svítidla LED HIGH BAY / SK: Priemyselná lampa / EN: LED high bay



INDEX	ABC				PF	Tc[K]		A [mm]	B [mm]	
045570	KARADAM LED	100 W	10 000 lm	100lm/W	0.9	4000 K	Czarny Černá Čierná Black	250	30	5902808809401
045571	KARADAM LED	150 W	15 000 lm	100lm/W	0.9	4000 K		300	30	5902808809418
045572	KARADAM LED	200 W	20 000 lm	100lm/W	0.9	4000 K		330	40	5902808809425

AC 230V	SMD LED	110°	NON-DIM
80	70000 h	65	04
RoHS COMPLIANT	CE	RoHS COMPLIANT	RoHS COMPLIANT

Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25 ° C do + 60 ° C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25 ° C do + 60 ° C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25 ° C to + 60 ° C

humidity: <85% pressure: 690-1060 hPa

BroLux