


## NAŚWIETLACZ LED

CZ: veďl svĕtlomet / SK: vedie svetlomet / EN: LED floodlight



INDEX



PF



A

B

C



INDEX	ABC	Power	Lm	Lm/W	Beam	PF	Tc[K]	Beam	A [mm]	B [mm]	C [mm]	Barcode
013879	MADOR LED	200W	23 600 lm	118m/W	70°×140°	≥0,95	2700 K	Szary Śedá Śedá Grey	350	315	75	5902808807438



AC 230V

SMD3030

IN&OUT



IP



≥80

50000h

65



Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C do +60°C

humidity: <85% pressure: 690-1060 hPa

