

# MILAD – AC LED



## HIGH BAY LED


CZ: Průmyslová svítidla LED HIGH BAY / SK: Priemyselná lampa / EN: LED high bay



A



B



	INDEX	ABC	Power	Lm	PF	Tc [K]	Material	A [mm]	B [mm]	Barcode
A	004561	ACLED Milad	30W	2500lm	≥0.95	4500 K	Srebrny Stieborný stříbrná silver	Ø335	262	5902216720862
A	483	ACLED Milad	55 W	4600lm	≥0.95	4500 K		Ø335	262	5902216720879
B	004562	ACLED Milad	100W	9000lm	≥0.95	4500 K		Ø402	349	5902216720893
B	002051	ACLED Milad	100W	9000lm	≥0.95	5700 K		Ø402	349	5902216720886
B	004564	ACLED Milad	150W	13500lm	≥0.95	4500 K		Ø410	353	5902216720916
B	006287	ACLED Milad	150W	13500lm	≥0.95	5700 K		Ø410	353	5902216720909
B	006814	ACLED Milad	200W	20000lm	≥0.95	5700 K		Ø536	379	5902216732001

### Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -10°C do +25°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -10 ° C to + 25 ° C

humidity: <85% pressure: 690-1060 hPa



AC 230V	SMDLED	60°	
70	40000 h		