

# REDOM



## OPRAWY LED

CZ: LED svítidlo/ SK: LED svetidlo/ EN: LED lamp



	INDEX	ABC		Lm	Tc[K]		PF				
A	045929	Redom LED	24W	2160 lm	4000K	Biały Biała Bielá White	0,9	600	48	30	5902808811381
A	045931	Redom LED	42W	3780 lm	4000K		0,9	1200	48	30	5902808811411
B	045928	Redom LED	24W	2160 lm	4000K	Czarny Černá Čierny Black	0,9	600	48	30	5902808811398
B	045930	Redom LED	42W	3780 lm	3000K		0,9	1200	48	30	5902808811404
B	045932	Redom LED	42W	3780 lm	4000K		0,9	1200	48	30	5902808811428

AC 230V	SMD LED	109°	
CRI(Ra)	IP		
80	20		
CE	RoHS COMPLIANT		

### Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

### Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C to +60°C

humidity: <85% pressure: 690-1060 hPa

**BroLux**