

# TILLY DALI



## DOWNLIGHT LED

CZ: LED podsvícení / SK: LED podsvietenia/ EN: LED downlight



### CITIZEN



INDEX	ABC		Tc[K]				A [mm]	B [mm]	
013760	Tilly LED	30W	3000K	3000 lm	24°	Biały biła Bielá white	165	128	5902808805571

		PF	
AC 230V	SMD LED		
	IP	IK	
>80	20	07	

#### Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

#### Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C to +60°C

humidity: <85% pressure: 690-1060 hPa