

# TILLY



## DOWNLIGHT LED

CZ: LED podsvícení / SK: LED podsvietenia/ EN: LED downlight



### CITIZEN

INDEX	ABC		Tc[K]	Lm			A [mm]	B [mm]	
013623	Tilly LED	30W	3000K	3000 lm	24°	Biały biła Bielá white	165	128	5902808804222
012310	Tilly LED	30W	4000 K	3000 lm	24°		165	128	5902216793316
013626	Tilly LED	30W	4000K	3000 lm	24°	Czarny Černá Čierná Black	165	128	5902808804239
013625	Tilly LED	50W	3000K	5000 lm	38°	Biały biła Bielá white	188	154	5902808804246
013624	Tilly LED	50W	4000K	5000 lm	38°		188	154	5902808804253

		PF	
AC 230V	SMD LED		
	IP	IK	
CR I(Ra)			
>80	20	07	

#### Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

#### Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

#### Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C to +60°C

humidity: <85% pressure: 690-1060 hPa